



## Safety Data Sheet

Material Name: MULTI-USE LACQUER THINNER

SDS ID: 82410

### Section 1 - PRODUCT AND COMPANY IDENTIFICATION

**Material Name**

SAFETY-KLEEN MULTI-USE LACQUER THINNER

**Product Code**

6801, 16801

**Synonyms**

None

**Product Use**

Lacquer thinner. If this product is used in combination with other products, refer to the Safety Data Sheet for those products.

**Restrictions on Use**

This product is not for sale or use in the State of California.

**MANUFACTURER**

Safety-Kleen Systems, Inc.  
42 Longwater Drive  
Norwell, MA 02061-9149  
U.S.A.  
www.safety-kleen.com

**SUPPLIER**

Safety-Kleen Canada, Inc.  
25 Regan Road  
Brampton, Ontario, L1A 1B2  
Canada

Phone: 1-800-669-5740

Emergency Phone #: 1-800-468-1760

**Issue Date**

October 22, 2021

**Supersedes Date**

October 24, 2019

**Original Issue Date**

July 29, 1989

### Section 2 - HAZARDS IDENTIFICATION

**Classification in accordance with Schedule 1 of Hazardous Products Regulations (HPR) (SOR/2015-17) and paragraph (d) of 29 CFR 1910.1200**

Flammable Liquids - Category 2

Aspiration Hazard - Category 1

Acute Toxicity - Oral - Category 4

Acute Toxicity – Inhalation – Vapor – Category 4

Skin Corrosion/Irritation - Category 2

Serious Eye Damage/Eye Irritation - Category 2A

Germ Cell Mutagenicity - Category 1B

Carcinogenicity - Category 1A

Reproductive Toxicity - Category 1A

Specific target organ toxicity - Single exposure - Category 1 and Category 3

Specific target organ toxicity - Repeated exposure - Category 1 and Category 2

# Safety Data Sheet

Material Name: MULTI-USE LACQUER THINNER

SDS ID: 82410

## GHS Label Elements

### Symbol(s)



### Signal Word

Danger

### Hazard Statement(s)

Highly flammable liquid and vapor.

Harmful if swallowed. May be fatal if swallowed and enters airways.

Harmful if inhaled.

Causes skin irritation, serious eye irritation, and damage to organs (central nervous system, kidneys, liver, respiratory system, systemic toxicity, retina)

May cause genetic defects, cancer, drowsiness or dizziness, respiratory irritation.

May damage fertility or the unborn child.

Causes damage to organs through prolonged or repeated exposure. (central nervous system, kidneys, liver, peripheral nervous system, retina, respiratory system )

May cause damage to organs through prolonged or repeated exposure.(blood )

### Precautionary Statement(s)

#### Prevention

Keep away from heat/sparks/open flame/hot surfaces - No smoking. Keep container tightly closed.

Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area.

#### Response

In case of fire, use carbon dioxide, alcohol-resistant foam, dry chemical, water spray. IF exposed or concerned. Get medical advice/attention. IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs, get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Rinse mouth.

#### Storage

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

#### Disposal

Dispose of in accordance with all applicable federal, state and local regulations.

#### Statement(s) of Unknown Acute Toxicity

Oral 2.5% of the mixture consists of ingredient(s) of unknown acute toxicity.

#### Other Hazards

None known.

# Safety Data Sheet

Material Name: MULTI-USE LACQUER THINNER

SDS ID: 82410

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
108-88-3	Toluene	0-50
67-64-1	Acetone	10-30
64742-89-8	Solvent naphtha (petroleum), light aliphatic	0-35
67-63-0	Isopropyl alcohol	2-15
78-93-3	Methyl ethyl ketone	5-10
763-69-9	Ethyl 3-ethoxypropanoate	0-10
110-19-0	Isobutyl acetate	0-10
108-10-1	Methyl isobutyl ketone	2-5
1330-20-7	Xylenes (o-, m-, p- isomers)	0-5
67-56-1	Methyl alcohol	0-5
71-23-8	N-propyl alcohol	0-5
141-78-6	Ethyl acetate	0-5
123-86-4	n-Butyl acetate	0-5
64-17-5	Ethyl alcohol	0-1

Concentration ranges are used to express batch-to-batch variability in the production of the mixture.

## Section 4 - FIRST AID MEASURES

### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.

### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

### Ingestion

IF SWALLOWED: aspiration hazard. Do NOT induce vomiting. If vomiting occurs, keep head lower than hips to help prevent aspiration. Immediately call a POISON CENTER or doctor/physician. Rinse mouth.

### Most Important Symptoms/Effects

#### Acute

Harmful if swallowed, harmful if inhaled, skin irritation, eye irritation, central nervous system damage, central nervous system depression, kidney damage, liver damage, respiratory system damage, respiratory tract irritation, systemic toxicity, retina damage, aspiration hazard.

# Safety Data Sheet

Material Name: MULTI-USE LACQUER THINNER

SDS ID: 82410

## Delayed

Mutagenic effects, cancer, reproductive effects, central nervous system damage, kidney damage, liver damage, May cause peripheral nervous system damage, retina damage, respiratory system damage, blood disorders.

## Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

## Section 5 - FIRE FIGHTING MEASURES

### Extinguishing Media

#### Suitable Extinguishing Media

Carbon dioxide, alcohol-resistant foam, dry chemical, water spray.

#### Unsuitable Extinguishing Media

Do not use high-pressure water streams.

### Special Hazards Arising from the Chemical

Highly flammable liquid and vapor. Avoid friction, static electricity and sparks. The vapor is heavier than air. Vapors or gases may ignite at distant ignition sources and flash back. Empty containers may contain product residue. Product may be sensitive to static discharge, which could result in fire or explosion. Run-off to sewer may create a fire hazard.

### Hazardous Combustion Products

Decomposition and combustion materials may be toxic. Burning may produce phosgene, chlorides, chloroacetylenes, formaldehyde, peracetic acid, carbon monoxide and unidentified organic compounds.

### Fire Fighting Measures

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.

Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas.

Apply water from a protected location or from a safe distance. Dike for later disposal.

### Special Protective Equipment and Precautions for Firefighters

A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

## Section 6 - ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8. Avoid release to the environment.

### Methods and Materials for Containment and Cleaning Up

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. A vapor suppressing foam may be used to reduce vapors. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, sparkproof tool into a sealable container for disposal. Additionally, for large spills: Water spray may reduce vapor, but may not prevent ignition in closed spaces. Dike far ahead of liquid spill for collection and later disposal. There may be specific federal regulatory reporting requirements associated with spills, leaks, or releases of this product. Also see SECTION 15: REGULATORY INFORMATION.

# Safety Data Sheet

Material Name: MULTI-USE LACQUER THINNER

SDS ID: 82410

## Section 7 - HANDLING AND STORAGE

### Precautions for Safe Handling

Keep away from heat, sparks, or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean, sparkproof tools and explosion-proof equipment. When transferring product, metal containers, including trucks and tank cars, should be grounded and bonded. Do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes Skin clothing shoes. Do not smoke while using this product.

### Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Store containers below 120°F (49°C) Store in a dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from heat, flame, sparks, static electricity, or other sources of ignition; containers may explode and cause injury or death. Empty product containers may retain product residue and can be dangerous. See SECTION 14: TRANSPORTATION INFORMATION for Packing Group information.

### Incompatible Materials

Strong acids, strong oxidizing materials, alkalis, reducing agents, reactive halogens, reactive metals.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### Component Exposure Limits

<b>Toluene</b>	<b>108-88-3</b>
ACGIH:	20 ppm TWA
NIOSH:	100 ppm TWA ; 375 mg/m3 TWA; 150 ppm STEL ; 560 mg/m3 STEL 500 ppm IDLH
OSHA (US):	200 ppm TWA; 300 ppm Ceiling
Alberta	50 ppm TWA ; 188 mg/m3 TWA; Substance may be readily absorbed through intact skin
British Columbia, Nova Scotia, Prince Edward Island	20 ppm TWA
Manitoba	20 ppm TWA; Skin - potential for cutaneous absorption
New Brunswick	50 ppm TWA ; 188 mg/m3 TWA; Skin - potential for cutaneous absorption
Northwest Territories, Nunavut	50 ppm TWA; 60 ppm STEL; Skin notation
Ontario	20 ppm TWA; Skin notation
Quebec	50 ppm TWAEV ; 188 mg/m3 TWAEV; Skin designation

## Safety Data Sheet

**Material Name: MULTI-USE LACQUER THINNER**

**SDS ID: 82410**

Saskatchewan	50 ppm TWA; 60 ppm STEL; Potentially harmful after absorption through skin or mucous membranes
Yukon	100 ppm TWA ; 375 mg/m3 TWA; 150 ppm STEL ; 560 mg/m3 STEL; Skin notation
<b>Acetone</b>	<b>67-64-1</b>
ACGIH:	250 ppm TWA; 500 ppm STEL
NIOSH:	250 ppm TWA ; 590 mg/m3 TWA; 2500 ppm IDLH (10% LEL )
OSHA (US):	1000 ppm TWA ; 2400 mg/m3 TWA
Alberta	500 ppm TWA ; 1200 mg/m3 TWA; 750 ppm STEL ; 1800 mg/m3 STEL
British Columbia, Nova Scotia, Prince Edward Island	250 ppm TWA; 500 ppm STEL
Manitoba	250 ppm TWA
New Brunswick	500 ppm TWA ; 1188 mg/m3 TWA; 750 ppm STEL ; 1782 mg/m3 STEL
Northwest Territories, Nunavut, Ontario, Saskatchewan	500 ppm TWA; 750 ppm STEL
Quebec	500 ppm TWAEV ; 1190 mg/m3 TWAEV; 1000 ppm STEV ; 2380 mg/m3 STEV
Yukon	1000 ppm TWA ; 2400 mg/m3 TWA; 1250 ppm STEL ; 3000 mg/m3 STEL
<b>Isopropyl alcohol</b>	<b>67-63-0</b>
ACGIH:	200 ppm TWA; 400 ppm STEL
NIOSH:	400 ppm TWA ; 980 mg/m3 TWA; 500 ppm STEL ; 1225 mg/m3 STEL; 2000 ppm IDLH (10% LEL )
OSHA (US):	400 ppm TWA ; 980 mg/m3 TWA
Alberta	200 ppm TWA ; 492 mg/m3 TWA; 400 ppm STEL ; 984 mg/m3 STEL
British Columbia, Northwest Territories, Nova Scotia, Nunavut; Ontario, Prince Edward Island, Saskatchewan	200 ppm TWA; 400 ppm STEL
Manitoba	200 ppm TWA
New Brunswick	400 ppm TWA ; 983 mg/m3 TWA; 500 ppm STEL ; 1230 mg/m3 STEL

## Safety Data Sheet

**Material Name: MULTI-USE LACQUER THINNER**

**SDS ID: 82410**

Quebec	400 ppm TWAEV ; 985 mg/m3 TWAEV; 500 ppm STEV ; 1230 mg/m3 STEV
Yukon	400 ppm TWA ; 980 mg/m3 TWA; 500 ppm STEL ; 1225 mg/m3 STEL; Skin notation
<b>Methyl ethyl ketone</b>	<b>78-93-3</b>
ACGIH:	200 ppm TWA; 300 ppm STEL
NIOSH:	200 ppm TWA ; 590 mg/m3 TWA; 300 ppm STEL ; 885 mg/m3 STEL; 3000 ppm IDLH
OSHA (US):	200 ppm TWA ; 590 mg/m3 TWA
Alberta, New Brunswick	200 ppm TWA ; 590 mg/m3 TWA; 300 ppm STEL ; 885 mg/m3 STEL
British Columbia	50 ppm TWA; 100 ppm STEL
Manitoba	200 ppm TWA
Northwest Territories, Nova Scotia, Nunavut, Ontario, Prince Edward Island, Saskatchewan	200 ppm TWA; 300 ppm STEL
Quebec	50 ppm TWAEV ; 150 mg/m3 TWAEV; 100 ppm STEV ; 300 mg/m3 STEV
Yukon	200 ppm TWA ; 590 mg/m3 TWA; 250 ppm STEL ; 740 mg/m3 STEL
<b>Isobutyl acetate</b>	<b>110-19-0</b>
ACGIH:	50 ppm TWA; 150 ppm STEL
NIOSH:	150 ppm TWA ; 700 mg/m3 TWA 1300 ppm IDLH (10% LEL )
OSHA (US):	150 ppm TWA ; 700 mg/m3 TWA
Alberta, New Brunswick	150 ppm TWA ; 713 mg/m3 TWA
Manitoba	50 ppm TWA
Northwest Territories, Nunavut, Saskatchewan	150 ppm TWA; 188 ppm STEL
Nova Scotia, Prince Edward Island, British Columbia, Ontario	50 ppm TWA; 150 ppm STEL
Quebec	150 ppm TWAEV ; 713 mg/m3 TWAEV
Yukon	150 ppm TWA ; 700 mg/m3 TWA; 187 ppm STEL ; 875 mg/m3 STEL

## Safety Data Sheet

**Material Name: MULTI-USE LACQUER THINNER**

**SDS ID: 82410**

<b>Methyl isobutyl ketone</b>	<b>108-10-1</b>
ACGIH:	20 ppm TWA; 75 ppm STEL
NIOSH:	50 ppm TWA ; 205 mg/m3 TWA 75 ppm STEL ; 300 mg/m3 STEL 500 ppm IDLH
OSHA (US):	100 ppm TWA ; 410 mg/m3 TWA
Alberta, New Brunswick	50 ppm TWA ; 205 mg/m3 TWA; 75 ppm STEL ; 307 mg/m3 STEL
British Columbia, Nova Scotia, Ontario, Prince Edward Island, Saskatchewan	20 ppm TWA; 75 ppm STEL
Manitoba	20 ppm TWA
Northwest Territories, Nunavut	50 ppm TWA; 75 ppm STEL
Quebec	50 ppm TWAEV ; 205 mg/m3 TWAEV; 75 ppm STEV ; 307 mg/m3 STEV
Yukon	100 ppm TWA ; 410 mg/m3 TWA; 125 ppm STEL ; 510 mg/m3 STEL; Skin notation
<b>Xylenes (o-, m-, p- isomers)</b>	<b>1330-20-7</b>
ACGIH:	100 ppm TWA; 150 ppm STEL
OSHA (US):	100 ppm TWA ; 435 mg/m3 TWA
Alberta, New Brunswick	100 ppm TWA ; 434 mg/m3 TWA; 150 ppm STEL ; 651 mg/m3 STEL
British Columbia, Northwest Territories, Nova Scotia, Nunavut, Ontario, Prince Edward Island, Saskatchewan	100 ppm TWA; 150 ppm STEL
Manitoba	100 ppm TWA
Quebec	100 ppm TWAEV ; 434 mg/m3 TWAEV; 150 ppm STEV ; 651 mg/m3 STEV
Yukon	100 ppm TWA ; 435 mg/m3 TWA; 150 ppm STEL ; 650 mg/m3 STEL; Skin notation



## Safety Data Sheet

**Material Name: MULTI-USE LACQUER THINNER**

**SDS ID: 82410**

<b>Methyl alcohol</b>	<b>67-56-1</b>
ACGIH:	200 ppm TWA; 250 ppm STEL Skin - potential significant contribution to overall exposure by the cutaneous route
NIOSH:	200 ppm TWA ; 260 mg/m3 TWA 250 ppm STEL ; 325 mg/m3 STEL Potential for dermal absorption 6000 ppm IDLH
OSHA (US):	200 ppm TWA ; 260 mg/m3 TWA
Alberta	200 ppm TWA ; 262 mg/m3 TWA; 250 ppm STEL ; 328 mg/m3 STEL; Substance may be readily absorbed through intact skin
British Columbia, Northwest Territories; Nunavut; Ontario	200 ppm TWA; Skin notation; 250 ppm STEL
Manitoba	200 ppm TWA; Skin - potential for cutaneous absorption; Skin - potential significant contribution to overall exposure by the cutaneous route
New Brunswick	200 ppm TWA ; 262 mg/m3 TWA; 250 ppm STEL ; 328 mg/m3 STEL Skin - potential for cutaneous absorption
Nova Scotia	200 ppm TWA; 250 ppm STEL; Skin - potential significant contribution to overall exposure by the cutaneous route
Prince Edward Island	200 ppm TWA; 250 ppm STEL
Quebec	200 ppm TWAEV ; 262 mg/m3 TWAEV; 250 ppm STEV ; 328 mg/m3 STEV; Skin designation
Saskatchewan	200 ppm TWA; 250 ppm STEL; Potentially harmful after absorption through skin or mucous membranes
Yukon	200 ppm TWA ; 260 mg/m3 TWA; 250 ppm STEL ; 310 mg/m3 STEL; Skin notation
<b>Ethyl acetate</b>	<b>141-78-6</b>
ACGIH:	400 ppm TWA
NIOSH:	400 ppm TWA ; 1400 mg/m3 TWA 2000 ppm IDLH (10% LEL )
OSHA (US):	400 ppm TWA ; 1400 mg/m3 TWA
<b>Ethyl alcohol</b>	<b>64-17-5</b>
ACGIH:	1000 ppm STEL

## Safety Data Sheet

**Material Name: MULTI-USE LACQUER THINNER**

**SDS ID: 82410**

NIOSH:	1000 ppm TWA ; 1900 mg/m <sup>3</sup> TWA 3300 ppm IDLH (10% LEL )
OSHA (US):	1000 ppm TWA ; 1900 mg/m <sup>3</sup> TWA
Alberta; New Brunswick	1000 ppm TWA ; 1880 mg/m <sup>3</sup> TWA
British Columbia, Nova Scotia, Ontario, Prince Edward Island	1000 ppm STEL
Northwest Territories, Nunavut, Saskatchewan	1000 ppm TWA; 1250 ppm STEL
Quebec	1000 ppm TWAEV ; 1880 mg/m <sup>3</sup> TWAEV
Yukon	1000 ppm TWA ; 1900 mg/m <sup>3</sup> TWA; 1000 ppm STEL ; 1900 mg/m <sup>3</sup> STEL
<b>Ethyl 3-ethoxypropanoate</b>	<b>763-69-9</b>
Ontario	50 ppm TWA ; 300 mg/m <sup>3</sup> TWA
<b>n-Propyl alcohol</b>	<b>71-23-8</b>
ACGIH:	100 ppm TWA
NIOSH:	200 ppm TWA ; 500 mg/m <sup>3</sup> TWA; 250 ppm STEL ; 625 mg/m <sup>3</sup> STEL Potential for dermal absorption; 800 ppm IDLH
OSHA (US):	200 ppm TWA ; 500 mg/m <sup>3</sup> TWA
Alberta	200 ppm TWA ; 492 mg/m <sup>3</sup> TWA 400 ppm STEL ; 984 mg/m <sup>3</sup> STEL
British Columbia, Nova Scotia, Ontario, Prince Edward Island	100 ppm TWA
Manitoba	100 ppm TWA; Skin - potential for cutaneous absorption
New Brunswick	200 ppm TWA ; 492 mg/m <sup>3</sup> TWA; 250 ppm STEL ; 614 mg/m <sup>3</sup> STEL; Skin - potential for cutaneous absorption
Northwest Territories, Nunavut, Saskatchewan	200 ppm TWA; 400 ppm STEL
Quebec	200 ppm TWAEV ; 492 mg/m <sup>3</sup> TWAEV; 250 ppm STEV ; 614 mg/m <sup>3</sup> STEV; Skin designation
Yukon	200 ppm TWA ; 500 mg/m <sup>3</sup> TWA; 250 ppm STEL ; 625 mg/m <sup>3</sup> STEL; Skin notation
<b>N-Butyl acetate</b>	<b>123-86-4</b>
ACGIH:	50 ppm TWA; 150 ppm STEL

## Safety Data Sheet

**Material Name: MULTI-USE LACQUER THINNER**

**SDS ID: 82410**

NIOSH:	150 ppm TWA ; 710 mg/m <sup>3</sup> TWA; 200 ppm STEL ; 950 mg/m <sup>3</sup> STEL; 1700 ppm IDLH (10% LEL )
OSHA (US):	150 ppm TWA ; 710 mg/m <sup>3</sup> TWA
Alberta; New Brunswick	150 ppm TWA ; 713 mg/m <sup>3</sup> TWA; 200 ppm STEL ; 950 mg/m <sup>3</sup> STEL
British Columbia; Nova Scotia; Ontario; Prince Edward Island	50 ppm TWA; 150 ppm STEL
Manitoba	50 ppm TWA
Northwest Territories; Nunavut; Saskatchewan	150 ppm TWA; 200 ppm STEL
Quebec	50 ppm TWAEV; 150 ppm STEV
Yukon	150 ppm TWA ; 710 mg/m <sup>3</sup> TWA 200 ppm STEL ; 950 mg/m <sup>3</sup> STEL

### ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

#### **Toluene (108-88-3)**

0.02 mg/l Medium: blood Time: prior to last shift of workweek Parameter: Toluene ; 0.03 mg/l Medium: urine Time: end of shift Parameter: Toluene ; 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background )

#### **Acetone (67-64-1)**

25 mg/l Medium: urine Time: end of shift Parameter: Acetone (nonspecific )

#### **Isopropyl alcohol (67-63-0)**

40 mg/l Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific )

#### **Methyl ethyl ketone (78-93-3)**

2 mg/l Medium: urine Time: end of shift Parameter: MEK (nonspecific )

#### **Methyl isobutyl ketone (108-10-1)**

1 mg/l Medium: urine Time: end of shift Parameter: MIBK

#### **Xylenes (o-, m-, p- isomers) (1330-20-7)**

1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids

#### **Methyl alcohol (67-56-1)**

15 mg/l Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific )

### Engineering Controls

Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits. Use explosion-proof equipment. Ensure compliance with applicable exposure limits.

### Individual Protection Measures, such as Personal Protective Equipment

#### Eye/face protection

Wear safety glasses. Additional protection like goggles, face shields, or respirators may be needed dependent upon anticipated use and concentrations of mists or vapors. Eye wash fountain and emergency showers are recommended. Contact lens use is not recommended.

# Safety Data Sheet

Material Name: MULTI-USE LACQUER THINNER

SDS ID: 82410

## Respiratory Protection

A respiratory protection program which meets USA's OSHA General Industry Standard 29 CFR 1910.134 or Canada's CSA Standard Z94.4-M1982 requirements must be followed whenever workplace conditions warrant a respirator's use. Consult a qualified Industrial Hygienist or Safety Professional for respirator selection guidance.

## Skin Protection/Glove Recommendations

To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant faceshield, boots, apron, whole body suits, or other protective clothing.

Where skin contact is likely, wear laminate (Ansell Edmont Barrier®, North Silver Shield®, Safety 4 4h®) or equivalent protective gloves; use of natural rubber (latex), polyvinyl chloride (PVC), neoprene or equivalent gloves is not recommended.

## Protective Materials

Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: Safety glasses, Gloves, and Lab coat or apron.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Liquid.	<b>Physical State</b>	Liquid
<b>Odor</b>	Solvent.	<b>Color</b>	Colorless.
<b>Odor Threshold</b>	Not available	<b>pH</b>	Not available
<b>Melting Point</b>	Not available	<b>Boiling Point</b>	56 - 172 °C (133 - 342 °F)
<b>Boiling Point Range</b>	Not available	<b>Freezing point</b>	Not available
<b>Evaporation Rate</b>	Not available	<b>Flammability (solid, gas)</b>	Not available
<b>Autoignition Temperature</b>	377 °C (711 °F Minimum)	<b>Flash Point</b>	<-7 °C [Closed Cup. ] (20 °F)
<b>Lower Explosive Limit</b>	1 vol% (Minimum)	<b>Decomposition temperature</b>	Not available
<b>Upper Explosive Limit</b>	36 vol% (Maximum)	<b>Vapor Pressure</b>	Not available
<b>Vapor Density (air=1)</b>	5 (Maximum Air = 1)	<b>Specific Gravity (water=1)</b>	0.84 (Water = 1)
<b>Water Solubility</b>	(Slight)	<b>Partition coefficient: n-octanol/water</b>	Not available
<b>Viscosity</b>	Not available	<b>Kinematic viscosity</b>	Not available
<b>Solubility (Other)</b>	Not available	<b>Coefficient of Water/Oil Dist</b>	2.73 (Toluene)
<b>Density</b>	7 lb/gal (US)	<b>Physical Form</b>	Liquid.
<b>Volatile Organic Compounds (As regulated)</b>	70 to 85 WT%; 5 to 6 LB/US gal (590 to 720 g/l) As per 40 CFR Part 51.100(s). Contains photochemically reactive solvent. VOC Vapor Pressure = 400 mm Hg @ 20°C Consult your state or local air district for location specific information.		

# Safety Data Sheet

Material Name: MULTI-USE LACQUER THINNER

SDS ID: 82410

<b>Molecular Weight</b>	Not available.	<b>OSHA Flammability Category</b>	Flammable
-------------------------	----------------	-----------------------------------	-----------

## Section 10 - STABILITY AND REACTIVITY

### Reactivity

No reactivity hazard is expected.

### Chemical Stability

Stable at normal temperatures and pressure.

### Possibility of Hazardous Reactions

Will not polymerize.

### Conditions to Avoid

Avoid Heat sparks or flame Avoid contact with incompatible materials.

### Incompatible Materials

Acids, alkalis, oxidizing agents, reducing agents, reactive halogens, or reactive metals.

### Hazardous decomposition products

Not applicable under normal conditions of use and storage. See also SECTION 5: HAZARDOUS COMBUSTION PRODUCTS.

## Section 11 - TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

#### Inhalation

May cause respiratory tract irritation.

#### Skin Contact

Causes skin irritation.

#### Eye Contact

Causes serious eye irritation.

#### Ingestion

Aspiration Hazard. Harmful if swallowed

### Acute and Chronic Toxicity

#### Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

##### **Toluene (108-88-3)**

Oral LD50 Rat 2600 mg/kg; Dermal LD50 Rabbit 12000 mg/kg; Inhalation LC50 Rat 12.5 mg/L 4 h

##### **Acetone (67-64-1)**

Oral LD50 Rat 5800 mg/kg; Dermal LD50 Rabbit >15700 mg/kg; Inhalation LC50 Rat 50100 mg/m<sup>3</sup> 8 h

##### **Solvent naphtha (petroleum), light aliphatic (64742-89-8)**

Oral LD50 Mouse 5000 mg/kg; Dermal LD50 Rabbit 3000 mg/kg

##### **Isopropyl alcohol (67-63-0)**

Oral LD50 Rat 1870 mg/kg; Dermal LD50 Rabbit 4059 mg/kg; Inhalation LC50 Rat >10000 ppm 6 h (no deaths occurred )

##### **Methyl ethyl ketone (78-93-3)**

Oral LD50 Rat 2483 mg/kg; Dermal LD50 Rabbit 5000 mg/kg; Inhalation LC50 Rat 11700 ppm 4 h

##### **Ethyl 3-ethoxypropanoate (763-69-9)**

Oral LD50 Rat 5 g/kg; Dermal LD50 Rabbit >9500 mg/kg; Inhalation LC50 Rat >5.96 mg/L 6 h (no deaths occurred )

##### **Isobutyl acetate (110-19-0)**

Oral LD50 Rat 15400 mg/kg; Dermal LD50 Rabbit >17400 mg/kg

# Safety Data Sheet

**Material Name: MULTI-USE LACQUER THINNER**

**SDS ID: 82410**

**Methyl isobutyl ketone (108-10-1)**

Oral LD50 Rat 2080 mg/kg; Dermal LD50 Rabbit 3000 mg/kg; Inhalation LC50 Rat 2000 - 4000 ppm 4 h

**Xylenes (o-, m-, p- isomers) (1330-20-7)**

Oral LD50 Rat 3500 mg/kg; Dermal LD50 Rabbit >4350 mg/kg; Inhalation LC50 Rat 29.08 mg/L 4 h

**Methyl alcohol (67-56-1)**

Oral LD50 Rat 6200 mg/kg; Dermal LD50 Rabbit 15840 mg/kg; Inhalation LC50 Rat 22500 ppm 8 h

**Ethyl acetate (141-78-6)**

Oral LD50 Rat 5620 mg/kg; Dermal LD50 Rabbit >18000 mg/kg; Inhalation LC50 Rat 4000 ppm 4 h

**Ethyl alcohol (64-17-5)**

Oral LD50 Rat 7060 mg/kg; Inhalation LC50 Rat 116.9 mg/L 4 h (males )

**n-Butyl acetate (123-86-4)**

Oral LD50 Rat 10768 mg/kg

Dermal LD50 Rabbit >17600 mg/kg

Inhalation LC50 Rat 0.74 mg/L 4 h

**Product Toxicity Data**

**Acute Toxicity Estimate**

Dermal	> 2000 mg/kg
Oral	> 2000 mg/kg

**Immediate Effects**

Harmful if swallowed, skin irritation, eye irritation, central nervous system damage, central nervous system depression, kidney damage, liver damage, respiratory system damage, respiratory tract irritation, systemic toxicity, retina damage, aspiration hazard

**Delayed Effects**

Mutagenic effects, cancer, reproductive effects, central nervous system damage, kidney damage, liver damage, May cause peripheral nervous system damage, retina damage, respiratory system damage, blood disorders

**Irritation/Corrosivity Data**

Eye irritation, skin irritation, respiratory tract irritation.

**Respiratory Sensitization**

No information available for the product.

**Dermal Sensitization**

No information available for the product.

**Component Carcinogenicity**

<b>Toluene</b>	<b>108-88-3</b>
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
IARC:	Monograph 71 [1999] ; Monograph 47 [1989] (Group 3 (not classifiable))
<b>Acetone</b>	<b>67-64-1</b>
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
<b>Isopropyl alcohol</b>	<b>67-63-0</b>
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
IARC:	Monograph 71 [1999] ; Supplement 7 [1987] ; Monograph 15 [1977] (Group 3 (not classifiable))

## Safety Data Sheet

Material Name: **MULTI-USE LACQUER THINNER**

SDS ID: 82410

<b>Methyl isobutyl ketone</b>	<b>108-10-1</b>
ACGIH:	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
IARC:	Monograph 101 [2013] (Group 2B (possibly carcinogenic to humans))
OSHA:	Present
<b>Xylenes (o-, m-, p-isomers)</b>	<b>1330-20-7</b>
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
IARC:	Monograph 71 [1999] ; Monograph 47 [1989] (Group 3 (not classifiable))
<b>Ethyl alcohol</b>	<b>64-17-5</b>
ACGIH:	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
DFG:	Category 5 (low carcinogenic potency )

**Germ Cell Mutagenicity**

Possible mutagen.

**Tumorigenic Data**

No data available

**Reproductive Toxicity**

Available data characterizes this substance as a reproductive hazard.

**Specific Target Organ Toxicity - Single Exposure**

Central nervous system, kidneys, liver, respiratory system, systemic toxicity, retina.

**Specific Target Organ Toxicity - Repeated Exposure**

Central nervous system, kidneys, liver, Peripheral Nervous System, retina, respiratory system, blood.

**Aspiration hazard**

This material is an aspiration hazard.

**Medical Conditions Aggravated by Exposure**

blood disorders, central nervous system disorders, eye disorders, kidney disorders, liver disorders, respiratory disorders, skin disorders, peripheral nervous system disorders, systemic disorders

<b>Section 12 - ECOLOGICAL INFORMATION</b>
--

**Ecotoxicity**

Toxic to aquatic life. Harmful aquatic life with long lasting effects.

**Component Analysis - Aquatic Toxicity**

<b>Toluene</b>	<b>108-88-3</b>
Fish:	LC50 96 h Pimephales promelas 15.22 - 19.05 mg/L [flow-through ] (1 day old ); LC50 96 h Pimephales promelas 12.6 mg/L [static ]; LC50 96 h Oncorhynchus mykiss 5.89 - 7.81 mg/L [flow-through ]; LC50 96 h Oncorhynchus mykiss 14.1 - 17.16 mg/L [static ]; LC50 96 h Oncorhynchus mykiss 5.8 mg/L [semi-static ]; LC50 96 h Lepomis macrochirus 11 - 15 mg/L [static ]; LC50 96 h Oryzias latipes 54 mg/L [static ]; LC50 96 h Poecilia

## Safety Data Sheet

**Material Name: MULTI-USE LACQUER THINNER**

**SDS ID: 82410**

	reticulata 28.2 mg/L [semi-static ] ; LC50 96 h Poecilia reticulata 50.87 - 70.34 mg/L [static ]
Algae:	EC50 96 h Pseudokirchneriella subcapitata >433 mg/L IUCLID ; EC50 72 h Pseudokirchneriella subcapitata 12.5 mg/L [static ] EPA
Invertebrate:	EC50 48 h Daphnia magna 5.46 - 9.83 mg/L [Static ] EPA ; EC50 48 h Daphnia magna 11.5 mg/L IUCLID
<b>Acetone</b>	<b>67-64-1</b>
Fish:	LC50 96 h Oncorhynchus mykiss 4.74 - 6.33 mL/L; LC50 96 h Pimephales promelas 6210 - 8120 mg/L [static ] ; LC50 96 h Lepomis macrochirus 8300 mg/L
Invertebrate:	EC50 48 h Daphnia magna 10294 - 17704 mg/L [Static ] EPA ; EC50 48 h Daphnia magna 12600 - 12700 mg/L IUCLID
<b>Solvent naphtha (petroleum), light aliphatic</b>	<b>64742-89-8</b>
Algae:	EC50 72 h Pseudokirchneriella subcapitata 4700 mg/L IUCLID
<b>Isopropyl alcohol</b>	<b>67-63-0</b>
Fish:	LC50 96 h Pimephales promelas 9640 mg/L [flow-through ] ; LC50 96 h Pimephales promelas 11130 mg/L [static ] ; LC50 96 h Lepomis macrochirus >1400000 µg/L
Algae:	EC50 96 h Desmodesmus subspicatus >1000 mg/L IUCLID ; EC50 72 h Desmodesmus subspicatus >1000 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna 13299 mg/L IUCLID
<b>Methyl ethyl ketone</b>	<b>78-93-3</b>
Fish:	LC50 96 h Pimephales promelas 3130 - 3320 mg/L [flow-through ]
Invertebrate:	EC50 48 h Daphnia magna >520 mg/L IUCLID ; EC50 48 h Daphnia magna 5091 mg/L IUCLID ; EC50 48 h Daphnia magna 4025 - 6440 mg/L [Static ] EPA
<b>Ethyl 3-ethoxypropanoate</b>	<b>763-69-9</b>
Fish:	LC50 96 h Pimephales promelas 62 mg/L [static ]
Invertebrate:	EC50 48 h Daphnia magna 970 mg/L IUCLID
<b>Isobutyl acetate</b>	<b>110-19-0</b>



## Safety Data Sheet

Material Name: **MULTI-USE LACQUER THINNER**

SDS ID: **82410**

Fish:	LC50 96 h <i>Oryzias latipes</i> 17 mg/L
<b>Methyl isobutyl ketone</b>	<b>108-10-1</b>
Fish:	LC50 96 h <i>Pimephales promelas</i> 496 - 514 mg/L [flow-through ]
Algae:	EC50 96 h <i>Pseudokirchneriella subcapitata</i> 400 mg/L IUCLID
Invertebrate:	EC50 48 h <i>Daphnia magna</i> 170 mg/L IUCLID
<b>Xylenes (o-, m-, p-isomers)</b>	<b>1330-20-7</b>
Fish:	LC50 96 h <i>Pimephales promelas</i> 13.4 mg/L [flow-through ]; LC50 96 h <i>Oncorhynchus mykiss</i> 2.661 - 4.093 mg/L [static ]; LC50 96 h <i>Oncorhynchus mykiss</i> 13.5 - 17.3 mg/L; LC50 96 h <i>Lepomis macrochirus</i> 13.1 - 16.5 mg/L [flow-through ]; LC50 96 h <i>Lepomis macrochirus</i> 19 mg/L; LC50 96 h <i>Lepomis macrochirus</i> 7.711 - 9.591 mg/L [static ]; LC50 96 h <i>Pimephales promelas</i> 23.53 - 29.97 mg/L [static ]; LC50 96 h <i>Cyprinus carpio</i> 780 mg/L [semi-static ]; LC50 96 h <i>Cyprinus carpio</i> >780 mg/L; LC50 96 h <i>Poecilia reticulata</i> 30.26 - 40.75 mg/L [static ]
Invertebrate:	EC50 48 h water flea 3.82 mg/L; LC50 48 h <i>Gammarus lacustris</i> 0.6 mg/L
<b>Methyl alcohol</b>	<b>67-56-1</b>
Fish:	LC50 96 h <i>Pimephales promelas</i> 28200 mg/L [flow-through ]; LC50 96 h <i>Pimephales promelas</i> >100 mg/L [static ]; LC50 96 h <i>Oncorhynchus mykiss</i> 19500 - 20700 mg/L [flow-through ]; LC50 96 h <i>Oncorhynchus mykiss</i> 18 - 20 mL/L [static ]; LC50 96 h <i>Lepomis macrochirus</i> 13500 - 17600 mg/L [flow-through ]
<b>Ethyl acetate</b>	<b>141-78-6</b>
Fish:	LC50 96 h <i>Pimephales promelas</i> 220 - 250 mg/L [flow-through ]; LC50 96 h <i>Oncorhynchus mykiss</i> 484 mg/L [flow-through ]; LC50 96 h <i>Oncorhynchus mykiss</i> 352 - 500 mg/L [semi-static ]
Invertebrate:	EC50 48 h <i>Daphnia magna</i> 560 mg/L [Static ] EPA
<b>Ethyl alcohol</b>	<b>64-17-5</b>
Fish:	LC50 96 h <i>Oncorhynchus mykiss</i> 12 - 16 mL/L [static ]; LC50 96 h <i>Pimephales promelas</i> >100 mg/L [static ]; LC50 96 h <i>Pimephales promelas</i> 13400 - 15100 mg/L [flow-through ]
Invertebrate:	LC50 48 h <i>Daphnia magna</i> 9268 - 14221 mg/L IUCLID ; EC50 48 h <i>Daphnia magna</i> 2 mg/L [Static ] EPA
<b>n-Butyl acetate</b>	<b>123-86-4</b>

# Safety Data Sheet

Material Name: MULTI-USE LACQUER THINNER

SDS ID: 82410

Fish:	LC50 96 h Lepomis macrochirus 100 mg/L [static ]; LC50 96 h Pimephales promelas 17 - 19 mg/L [flow-through ]
Algae:	EC50 72 h Desmodesmus subspicatus 674.7 mg/L IUCLID

## Invertebrate Toxicity

No additional information is available.

## Persistence and Degradability

No information available for the product.

## Bioaccumulative Potential

No information available for the product.

## Mobility

No information available for the product.

## Section 13 - DISPOSAL CONSIDERATIONS

### Disposal Methods

Dispose of in accordance with all applicable federal, state and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Safety-Kleen regarding proper recycling or disposal.

## Section 14 - TRANSPORT INFORMATION

### US DOT Information:

**Shipping Name:** PAINT RELATED MATERIAL

**Hazard Class:** 3

**UN/NA #:** UN1263

**Packing Group:** II

**Required Label(s):** 3 FLAMMABLE LIQUID

### IATA Information:

**Shipping Name:** PAINT RELATED MATERIAL

**Hazard Class:** 3

**UN#:** UN1263

**Packing Group:** II

**Required Label(s):** 3 Flammable Liquid

### IMDG Information:

**Shipping Name:** PAINT RELATED MATERIAL

**Hazard Class:** 3

**UN#:** UN1263.

**Packing Group:** II

**Required Label(s):** 3 Flammable Liquid

### TDG Information:

**Shipping Name:** PAINT RELATED MATERIAL

**Hazard Class:** 3

**UN#:** UN1263

**Packing Group:** II

**Required Label(s):** 3 FLAMMABLE LIQUID

## Safety Data Sheet

**Material Name: MULTI-USE LACQUER THINNER**

**SDS ID: 82410**

### International Bulk Chemical Code

This material contains one or more of the following chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

<b>Toluene</b>	<b>108-88-3</b>
IBC Code:	Category Y
<b>Methyl ethyl ketone</b>	<b>78-93-3</b>
IBC Code:	Category Z
<b>Ethyl 3-ethoxypropanoate</b>	<b>763-69-9</b>
IBC Code:	Category Y
<b>Methyl isobutyl ketone</b>	<b>108-10-1</b>
IBC Code:	Category Z
<b>Xylenes (o-, m-, p- isomers)</b>	<b>1330-20-7</b>
IBC Code:	Category Y
<b>Methyl alcohol</b>	<b>67-56-1</b>
IBC Code:	Category Y
<b>Ethyl acetate</b>	<b>141-78-6</b>
IBC Code:	Category Z

### Further information

ERG128

## Section 15 - REGULATORY INFORMATION

### U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

<b>Toluene</b>	<b>108-88-3</b>
SARA 313:	1 % de minimis concentration
CERCLA:	1000 lb final RQ ; 454 kg final RQ
<b>Acetone</b>	<b>67-64-1</b>
CERCLA:	5000 lb final RQ ; 2270 kg final RQ
<b>Isopropyl alcohol</b>	<b>67-63-0</b>

## Safety Data Sheet

**Material Name: MULTI-USE LACQUER THINNER**

**SDS ID: 82410**

SARA 313:	1 % de minimis concentration (only if manufactured by the strong acid process, no supplier notification )
<b>Methyl ethyl ketone</b>	<b>78-93-3</b>
CERCLA:	5000 lb final RQ ; 2270 kg final RQ
<b>Isobutyl acetate</b>	<b>110-19-0</b>
CERCLA:	5000 lb final RQ ; 2270 kg final RQ
<b>Methyl isobutyl ketone</b>	<b>108-10-1</b>
SARA 313:	0.1 % de minimis concentration
CERCLA:	5000 lb final RQ ; 2270 kg final RQ
<b>Xylenes (o-, m-, p- isomers)</b>	<b>1330-20-7</b>
SARA 313:	1 % de minimis concentration
CERCLA:	100 lb final RQ ; 45.4 kg final RQ
<b>Methyl alcohol</b>	<b>67-56-1</b>
SARA 313:	1 % de minimis concentration
CERCLA:	5000 lb final RQ ; 2270 kg final RQ
<b>Ethyl acetate</b>	<b>141-78-6</b>
CERCLA:	5000 lb final RQ ; 2270 kg final RQ
<b>n-Butyl acetate</b>	<b>123-86-4</b>
CERCLA:	5000 lb final RQ ; 2270 kg final RQ

Chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

CAS-No.	Name	Percent by Weight
108-88-34	Toluene	0-50
67-63-0	Isopropyl alcohol	2-15
108-10-1	Methyl isobutyl ketone	2-5
1330-20-7	Xylenes (o-, m-, p- isomers)	0-5
67-56-1	Methyl alcohol	0-5

# Safety Data Sheet

**Material Name: MULTI-USE LACQUER THINNER**

**SDS ID: 82410**

**SARA Section 311/312 (40 CFR 370 Subparts B and C) reporting categories**

Flammable; Carcinogenicity; Acute toxicity; Reproductive Toxicity; Skin Corrosion/Irritation; Serious Eye Damage/Eye Irritation; Specific Target Organ Toxicity; Aspiration Hazard; Germ Cell Mutagenicity

**U.S. State Regulations**

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
<b>Toluene</b>	<b>108-88-3</b>	Yes	Yes	Yes	Yes	Yes
<b>Acetone</b>	<b>67-64-1</b>	Yes	Yes	Yes	Yes	Yes
<b>Isopropyl alcohol</b>	<b>67-63-0</b>	Yes	Yes	Yes	Yes	Yes
<b>Methyl ethyl ketone</b>	<b>78-93-3</b>	Yes	Yes	Yes	Yes	Yes
<b>Isobutyl acetate</b>	<b>110-19-0</b>	Yes	Yes	Yes	Yes	Yes
<b>Methyl isobutyl ketone</b>	<b>108-10-1</b>	Yes	Yes	Yes	Yes	Yes
<b>Xylenes (o-, m-, p- isomers)</b>	<b>1330-20-7</b>	Yes	Yes	Yes	Yes	Yes
<b>Methyl alcohol</b>	<b>67-56-1</b>	Yes	Yes	Yes	Yes	Yes
<b>Ethyl acetate</b>	<b>141-78-6</b>	Yes	Yes	Yes	Yes	Yes
<b>Ethyl alcohol</b>	<b>64-17-5</b>	Yes	Yes	Yes	Yes	Yes
<b>n-Butyl acetate</b>	<b>123-86-4</b>	Yes	Yes	Yes	Yes	Yes

**California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)**

This product is not for sale or use in the State of California.

**Component Analysis - Inventory**

**Toluene (108-88-3)**

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW, CN	VN (Draft)
Yes			Yes	Yes	Yes	Yes	Yes	Yes

**Acetone (67-64-1)**

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW, CN	VN (Draft)

# Safety Data Sheet

**Material Name: MULTI-USE LACQUER THINNER**

**SDS ID: 82410**

No	Yes	Yes	Yes	Yes	Yes	Yes
----	-----	-----	-----	-----	-----	-----

**Solvent naphtha (petroleum), light aliphatic (64742-89-8)**

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	No	No	Yes	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW, CN	VN (Draft)
No		Yes	Yes	Yes	No	Yes	Yes	

**Isopropyl alcohol (67-63-0)**

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW, CN	VN (Draft)
No		Yes	Yes	Yes	Yes	Yes	Yes	

**Methyl ethyl ketone (78-93-3)**

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW, CN	VN (Draft)
Yes		Yes	Yes	Yes	Yes	Yes	Yes	

**Ethyl 3-ethoxypropanoate (763-69-9)**

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW, CN	VN (Draft)
No		Yes	Yes	Yes	Yes	Yes	Yes	

# Safety Data Sheet

**Material Name: MULTI-USE LACQUER THINNER**

**SDS ID: 82410**

**Isobutyl acetate (110-19-0)**

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW, CN	VN (Draft)
No			Yes	Yes	Yes	Yes	Yes	Yes

**Methyl isobutyl ketone (108-10-1)**

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW, CN	VN (Draft)
No			Yes	Yes	Yes	Yes	Yes	Yes

**Xylenes (o-, m-, p- isomers) (1330-20-7)**

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW, CN	VN (Draft)
Yes			Yes	Yes	Yes	Yes	Yes	Yes

**Methyl alcohol (67-56-1)**

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW, CN	VN (Draft)
Yes			Yes	Yes	Yes	Yes	Yes	Yes

# Safety Data Sheet

**Material Name: MULTI-USE LACQUER THINNER**

**SDS ID: 82410**

**Ethyl acetate (141-78-6)**

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW, CN	VN (Draft)
Yes			Yes	Yes	Yes	Yes	Yes	Yes

**n-Butyl acetate (123-86-4)**

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW, CN	VN (Draft)
No			Yes	Yes	Yes	Yes	Yes	Yes

**Ethyl alcohol (64-17-5)**

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW, CN	VN (Draft)
No			Yes	Yes	Yes	Yes	Yes	Yes

## Section 16 - OTHER INFORMATION

**NFPA Ratings**

Health: 3 Fire: 3 Instability: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

**Summary of Changes**

Section 3: Composition / information on ingredients. Section 15.

**Key / Legend**

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania\*; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CFR - Code of Federal Regulations (US); CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC - European Commission; EEC - European Economic Community; EIN - European Inventory of (Existing Commercial Chemical Substances);



# Safety Data Sheet

Material Name: MULTI-USE LACQUER THINNER

SDS ID: 82410

EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; F - Background (for Venezuela Biological Exposure Indices); IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID - International Uniform Chemical Information Database; JP - Japan; Kow - Octanol/water partition coefficient; KR KECI Annex 1 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL); KR KECI Annex 2 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL), KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; KR REACH CCA - Korea Registration and Evaluation of Chemical Substances Chemical Control Act; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX - Mexico; Ne - Non-specific; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; Nq - Non-quantitative; NSL - Non-Domestic Substance List (Canada); NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH - Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; Sc - Semi-quantitative; STEL - Short-term Exposure Limit; TCCA - Korea Toxic Chemicals Control Act; TDG - Transportation of Dangerous Goods; TH-TECI - Thailand - FDA Existing Chemicals Inventory (TECI); TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW - Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; VLE - Exposure Limit Value (Mexico); VN (Draft) - Vietnam (Draft); WHMIS - Workplace Hazardous Materials Information System (Canada).

## Other Information

### Disclaimer:

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers. The data contained on this sheet apply to the product as supplied to the user.